

Anti-Ageing Moisturizer

Oil-in-Water Skin Cream: Anti-ageing, Long Lasting / Substantivity, Luxurious, dry, light feel

Formulation 00208

ATTRIBUTES

- Emolliency
- Good spreadability
- Anti-ageing
- Long Lasting / Substantivity
- Luxurious, dry, light feel

DOW CORNING® PRODUCTS

- DOW CORNING® 556 FLUID

XIAMETER® PRODUCTS

- XIAMETER® PMX-1501 FLUID

Ingredient	Wt. %	Trade Name/Supplier
Phase A		
1. Cetearyl Alcohol (and) Cetareth-20	3	Emulgade 1000 NI / Cognis corporation
2. Cetyl-Stearyl Alcohol	6	Hydrenol MY / Cognis corporation
3. Avocado oil unsaponifiables	3	Avocadine / Croda
4. Vegetable Oil	3	Evening Primrose Oil / Cosmetochem
5. C12-15 Alkyl Benzoate	3	Finsolv TN / (Witco Corporation)
6. Phenyl Trimethicone	2	DOW CORNING® 556 FLUID
7. Octyl Methoxycinnamate	2	Parsol MCX / DSM Nutritional Products
Phase B		
8. DL-Alpha Tocopheryl linoleate	1	
9. D-alpha Tocopherol Acetate	1	Covitol 1100 / Cognis Corporation, Care Chemicals
Phase C		
10. Panthenol	1	Panthenol 50P / BASF Corporation
11. Citric Acid	0.11	
12. Disodium EDTA	0.1	
13. Deionized Water	60.09	
Phase D		
14. Marine Extract	3	Plankton Extract / Provital
15. Cyclopentasiloxane (and) Dimethiconol	7	XIAMETER® PMX-1501 FLUID
16. Sodium Hydroxymethyl Glycinate	0.5	Suttocide A / ISP
17. Water (and) Mannitol (and) Lecithin (and) Borage Oil	2	Phosphosomes Cevenyl 11G / Gattefosse S.A.
Phase E		
18. Fagus SilvatICA Extract	1	Gatuline / Gattefosse S.A.
19. Fish collagen	1	Neptuline / Rousel Uclaf

Procedure

1. Mix ingredients of phase A together.
2. Heat to 75°C.
3. Mix phase C ingredients together.
4. Heat to 75°C.
5. Mix ingredients of phase B together.
6. Add phase B to A just before emulsification and mix in.
7. Add phase AB to phase C with high speed stirring (Silversone 2-3 minutes).
8. Transfer mixture to propeller mixer and begin cooling, while mixing with average speed
9. Continue mixing until temperature reduces to 45°C.
10. Add ingredients of phase D one after another and mix with the same speed
11. When T drops below 30 C, add ingredients of phase E one after another, while mixing at same. speed
12. Continue mixing at same speed to RT.

Variations

Alternative Dow Corning® Products have not been tested as of this printing.

Stability

Stable for at least 6 months at room temperature and 40°C.

External Reference Material

No external references identified as of this printing.

Dow Corning® Application Patents

This suggested formulation is only a representative formulation and it is not a commercialized product. Dow Corning believes that the information and data on which this formulation is based are reliable, but it has not been subjected to extensive testing for performance, efficacy or safety. BEFORE COMMERCIALIZATION, YOU SHOULD THOROUGHLY TEST THE FORMULATION OR ANY VARIATION OF IT TO DETERMINE ITS PERFORMANCE, EFFICACY AND SAFETY. IT IS YOUR RESPONSIBILITY TO OBTAIN ANY NECESSARY GOVERNMENT CLEARANCE, LICENSE OR REGISTRATION. In addition, Dow Corning has not undertaken a comprehensive patent search on the formulation. Suggestions of uses should not be taken as inducements to infringe any particular patent.

SAFE HANDLING INFORMATION

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED. BEFORE HANDLING, READ PRODUCT AND MATERIAL SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. FOR THE MATERIAL SAFETY DATA SHEET PLEASE SEE OUR WEB SITE, DOWCORNING.COM, OR CONSULT YOUR LOCAL DOW CORNING REPRESENTATIVE.

Dow Corning is a registered trademark of Dow Corning Corporation.
XIAMETER is a registered trademark of Dow Corning Corporation.

© 2010 Dow Corning Corporation. All rights reserved.